



US007111519B2

(12) **United States Patent**
Dille

(10) **Patent No.:** **US 7,111,519 B2**

(45) **Date of Patent:** **Sep. 26, 2006**

(54) **TUBE ASSEMBLY AND METHOD**

(75) Inventor: **Joseph C. Dille**, Telford, PA (US)

(73) Assignee: **Emerson Electric Co.**, St. Louis, MO (US)

4,895,031 A *	1/1990	Cage	73/861.355
5,253,520 A	10/1993	Drexel et al.	
5,344,717 A *	9/1994	Dutton et al.	428/598
5,405,176 A	4/1995	Babel et al.	
6,519,828 B1 *	2/2003	Cook et al.	29/447
6,634,241 B1	10/2003	Van Cleve	

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/707,078**

(22) Filed: **Nov. 19, 2003**

(65) **Prior Publication Data**

US 2005/0103122 A1 May 19, 2005

(51) **Int. Cl.**

G01F 1/84 (2006.01)

(52) **U.S. Cl.** **73/861.355**

(58) **Field of Classification Search** 73/861.354, 73/861.355, 861.356, 861.357

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,331,932 A	10/1943	Rowand
4,768,385 A	9/1988	Cage

OTHER PUBLICATIONS

PCT International Search Report for International Application No. PCT/US2004/038836 dated Jun. 2, 2005.

PCT Written Opinion of the International Searching Authority for International Application No. PCT/US2004/038836 dated Jun. 2, 2005.

* cited by examiner

Primary Examiner—Harshad Patel

(74) *Attorney, Agent, or Firm*—Locke Liddell & Sapp LLP

(57) **ABSTRACT**

A flow sensor tube assembly includes a base member having first and second generally opposing sides. An opening extends through the base member, and an end of a flow sensor tube is received in the opening. A filler material is situated in the opening surrounding the flow sensor tube adjacent the first side of the base member to attach the tube to the base member. The flow sensor tube is welded to the base member adjacent the second side of the base member.

13 Claims, 3 Drawing Sheets

